Glass Fiber Thermal Conductive Tape									
Introduction	Glass fiber thermal tape is made of glass fiber cloth as the base material and coated with high thermal conductivity acrylic adhesive. It has high thermal conductivity, good temperature resistance, good adhesion, and good insulation performance.								
Application	 Fix the CPU and heat sink or heat sink. Fix the LED strip, substrate and frame. Fix the electronic components and heat sink. 								
Property									
Product Code Technical Parameters	P8010	P8015	P8020	P8025	P8030	P8035	P8040	P8050	P8070
Color	White	White	White	White	White	White	White	White	White
Total Thickness[mm]	0.1	0. 15	0. 2	0. 25	0.3	0.35	0.4	0. 5	0.7
Backing Thickness[mm]	0.05	0.05	0. 1	0. 1	0. 1	0. 1	0.1	0. 1	0.1
Backing	Glass Fiber								
Adhesive	Acrylic								
180° Peel Strength[N/inch]	12	12	15	15	15	15	18	18	20
Initial Adhesion[#]	2	2	2	2	3	3	3	3	3
Thermal Conductivity[W/mk]	0.3~0.8								
Long-Term Temperature Resistance[℃]	80								
Short-Term Temperature Resistance[℃]	120								
Storage and shelf life	It is recommended to store in a clean and dry place, away from direct sunlight to prevent damage to the packaging, and to avoid storing with volatile solvents. Store at $25\pm5^\circ$ C and humidity at $50\pm5\%$.								