

MOPP Strapping Tape					
Introduction	MOPP Strapping Tape is made of high performance MOPP film coated with a special synthetic rubber/acrylate pressure sensitive adhesive. It has high adhesive strength, high Tensile Strength, low elongation, easy horizontal tearing and no adhesive residue removal.				
Application	1. Temporary fixing, encapsulation and reinforcement of moving parts of household appliances, refrigerators and air conditioners. 2. Tying and fixing of office accessories such as printers. 3. End fixing of metal pipe profiles.				
Property					
<div>Product Code</div> <div>Technical Parameters</div>	P4807L	P4810L	P4810H	P4810C	P48145
Color	Light Blue / Dark Blue / White	Light Blue / Dark Blue / White	Light Blue / Dark Blue / White	Light Blue / Dark Blue / White	Yellow
Total Thickness[mm]	0.75	0.1	0.1	0.1	0.145
Backing Thickness[mm]	0.05	0.08	0.08	0.08	0.115
Backing	MOPP	MOPP	MOPP	MOPP	MOPP
Adhesive	Rubber	Rubber	Rubber	Rubber	Acrylic
180° Peel Strength[N/inch]	7	8	13.8	8	9
Tensile Strength[N/inch]	340	500	475	600	700
Elongation At Break[%]	20	18	17	20	16
Retentivity[hour]	72	72	72	72	72
Long-Term Temperature Resistance[℃]	60	60	60	60	130
Short-Term Temperature Resistance[℃]	80	80	80	80	150
Storage and shelf life	It is recommended to store in a clean and dry place, away from direct sunlight to prevent damage to the packaging, and to avoid storing with volatile solvents. Store at 25±5° C and humidity at 50±5%.				