

PET wire harness tape		
Introduction	PET wire harness tape is made of knitted fabric (PET) as a base material coated with a high-performance acrylate pressure-sensitive adhesive. It has high strength and durability, flame retardancy, no shrinkage and no warping at high and low temperatures, and easy to tear.	
Application	1.It should be used for server and computer wiring harness bundling and fixing. 2.It is used in home appliances and display wiring harnesses bundled and fixed 3.It is used for automobile wiring harness bundling and fixing	
Property		
Product Code	P2016B	P2025B
Technical Parameters		
Color	Black	Black/Orange
Total Thickness [mm]	0.16	0.025
Backing	Woven PET	Woven PET
Adhesive	Acrylic adhesive	Acrylic adhesive
180° Peel Strength[N/inch]	1.5	2
Tensile Strength[N/inch]	50	160
Elongation at break[%]	10	15
Temperature resistance[°C]	-40 (4H) 105 (3000H) 130 (240H)	-40 (4H) 125 (3000H) 150 (240H)
Noise reduction performance	Class A ≤2dB	Class A ≤2dB
Abrasion resistance (Scrape)	Class B 100-499	Class B 100-499
Flame retardation	Class B self-extinguishing	Class B self-extinguishing
Storage and shelf life	It is recommended to store in a clean and dry place, away from direct sunlight, to prevent damage to the packaging, and to avoid keeping it with volatile solvents. The storage temperature is 10-40° C and the humidity is 40-60%. To maintain optimal performance, this product should be used within 12 months from the date of manufacture.	