

Double Sided PVC Tape			
Introduction	Double Sided PVC Tape is made of PVC as the base material, coated with acrylate glue on both sides, and then compounded with release film/release paper. It has good flexibility, good ductility, suitable for sticking on uneven surfaces, temperature resistance, and moisture resistance, and has high bonding strength to rough surfaces and non-tough surfaces.		
Application	Suitable for pasting between the exterior heat-resistant lens and the fixed plate of the car, and the pasting of furniture modules and decorative parts. It has better effect on the surface of various materials (PP, PE, PVC, ABS, PC, aluminum, steel) Adhesion.		
Property			
<div>Product Code</div> <div>Technical Parameters</div>	P3423	P3425	P3432
Color	Milky White	Milky White	Milky White
Total Thickness[mm]	0.225	0.25	0.325
Backing	PVC	PVC	PVC
Adhesive	Acrylic	Acrylic	Acrylic
180° Peel Strength[N/inch]	16	18	20
Initial Tack[mm]	≤100	≤100	≤100
Retentivity[hour]	≥24	≥24	≥24
Long-Term Temperature Resistance [°C]	60	60	60
Short-Term Temperature Resistance [°C]	80	80	80
Storage and shelf life	It is recommended to store in a clean and dry place, away from direct sunlight to prevent damage to the packaging, and to avoid storing with volatile solvents. Store at 25±5° C and humidity at 50±5%.		