

Warning Tape		
Introduction	Warning tape is made of PVC film and coated with special high performance rubber. It has good flexibility, good Tensile Strength, high abrasion resistance, colour diversity, no fading, long lasting adhesion, repeatable positioning, acid and alkali resistance, water resistance, friction resistance, and no residual adhesive after a long time of lamination.	
Application	1.Factory workshop, machinery and equipment, supermarkets and other limited space to divide the area, play a role in marking. 2.Temporary protection in the process of electroplating and painting industry. 3.Wrapping and wrapping of pipelines for oil, natural gas, gas, etc. 4.Traffic lane and safety marking applications. 5.Colour coded metal cans and storage containers for sealing and reinforcing decoration.	
Property		
<div>Product Code</div> <div>Technical Parameters</div>	P2100	P2100D
Color	Black, Red, Green, Yellow, White,Blue	Black And Yellow, Red And White, Blue And White, Green And White, Black And White
Total Thickness[mm]	0.13~0.16	0.13~0.16
Backing	PVC	PVC
Adhesive	Rubber	Rubber
180° Peel Strength[N/inch]	4.5	4
Tensile Strength[N/inch]	65.4	85
Elongation At Break[%]	200	200
Long-Term Temperature Resistance[℃]	80	80
Short-Term Temperature Resistance[℃]	100	100
Storage and shelf life	It is recommended to store in a clean and dry place, away from direct sunlight to prevent damage to the packaging, and to avoid storing with volatile solvents. Store at 25±5° C and humidity at 50±5%.	