		Wł	nite non	-woven t	ape			
Introduction	White non-woven tape is made of polyester film composite non-woven fabric as the base material, and acrylic pressure-sensitive adhesive is evenly coated on the non-woven fabric. It has the characteristics of high insulation, high breakdown voltage resistance, and good temperature resistance							
Application	 Insulation of UPS power supplies, dry-type transformers, high temperature frequency transformers, gaskets (high temperature), microwave oven transformers. Insulation of transformers, electronic coils, motors and other electronic industries. 							
Property								
Product Code Technical Parameters	P2314-1	P2315	P2320	P2323	P2324	P2328	P2335	P2340
Color	White	White	White	White	White	White	White	White
Total Thickness [mm]	0.14	0.15	0.2	0.23	0.24	0. 28	0.35	0.4
Backing	PET Laminated Non-Woven	PET Laminated Non-Woven	PET Laminated Non-Woven	PET Laminated Non-Woven	l PET Laminated Non-Woven	PET Laminated Non-Woven	PET Laminated Non-Woven	PET Laminated Non-Woven
Adhesive	Acrylic	Acrylic	Acrylic	Acrylic	Acrylic	Acrylic	Acrylic	Acrylic
180° Peel Strength[N/inch]	≥ 5							
Breakdown Voltage[KV]	≥4.5	≥4.5	≥4.5	≥4.5	≥4.5	≥4.5	≥ 5	≥5
Tensile Strength[N/inch]	≥3.8	3.8	3. 8	3.8	3.8	3.8	3.8	3.8
Elongation At Break[%]	≥40	≥40	≥40	≥40	≥40	≥40	≥40	≥40
Temperature resistance[℃]	130							
Cold hardiness[℃]	≤-10							
SOLVENT RESISTANCE	ОК							
Storage and shelf life	It is recommended to store in a clean and dry place, away from direct sunlight, to prevent damage to the packaging, and to avoid keeping it with volatile solvents. The storage temperature is $0-40^{\circ}$ C and the humidity is <80%. To maintain optimal performance, this product should be used within 12 months from the date of manufacture.							