ICIIOM DADCI. DIACK ILI UDUDIC BIUCU CADC	Yellow paper,	black	PET	double-	sided	tape
---	---------------	-------	-----	---------	-------	------

	reflow paper, black FET double-sided tape
Introduction	Yellow paper black PET double-sided tape is made of transparent PET film as the base material and coated with special acrylic pressure-sensitive adhesive on both sides. It has excellent adhesion, good initial tack and stickiness, good high humidity resistance, excellent aging resistance, excellent shear resistance at high and low temperatures, and strong tensile resistance.
Application	 Used for pasting of backlight modules, fixing and pasting of electronic and electrical components, dust-proof nets, LED reflection molds and other parts. Bonding and fixing of nameplates and membrane switches in the home appliance industry. Paste and fix FPC. Paste and fix the internal structure of OLED. The module is fixed by pasting the protective film. Temporary fixing and pasting of mobile phone parts. Paste the graphite sheet inside the mobile phone. Paste and fix the rubber feet. Paste the sprayed board on the mesh surface of the microwave oven door.

Property

Product Code	Color	Total Thickness [um]	Backing [mm]	Adhesive	Initial Tack [mm]	180° Peel Strength [N/inch]	Retentivity [hour]	Long-Term Temperature Resistance [℃]	Short-Term Temperature Resistance [℃]
P3203B	Black	30	0.012	Acrylic	≤150	≥7	≥24	80	120
P3205B	Black	50	0.012	Acrylic	≤150	≥8	≥24	80	120
Р3208В	Black	80	0.012	Acrylic	≤120	≥10	≥24	80	120
P3210B	Black	100	0.012	Acrylic	≤100	≥12	≥24	80	120
P3213B	Black	125	0.012	Acrylic	≤100	≥14	≥24	80	120
P3216B	Black	160	0.012	Acrylic	≤100	≥15	≥24	80	120
Р3220В	Black	205	0.012	Acrylic	≤100	≥17	≥24	80	120
	I								

Storage and shelf life

It is recommended to store in a clean and dry place, away from direct sunlight to prevent damage to the packaging, and to avoid storing with volatile solvents. Store at $25\pm5^{\circ}$ C and humidity at $50\pm5\%$.